

---

**RANGE SUMMARY**

---

The EnerSys<sup>®</sup> range of PowerSafe<sup>®</sup> SBS batteries continues to offer unrivalled choice and performance in compact and energy dense configurations. PowerSafe SBS batteries are manufactured to the highest international standards and are ideal for reliable use in all wireless and fixed-line communication applications. PowerSafe SBS batteries are also widely used in cable TV, emergency lighting, power generation and offshore applications.

The PowerSafe SBS battery range is available in several configurations including the front terminal series, which has become extremely popular in leading edge telecom applications. Smaller than the competition, the design of the front terminal series offers improved flexibility where space is limited and makes installation and maintenance easier and faster.

PowerSafe SBS batteries are designed to cope with raised temperatures and harsh environments. The advanced pure lead plate technology and unique manufacturing methods used by EnerSys, make PowerSafe SBS batteries the first choice for long and trouble-free service. The maximum operating temperature of the PowerSafe SBS J battery series can be extended to 80°C via an optional metal jacket.

**Features & Benefits**

- Capacity range: 7Ah - 360Ah
- 2V, 6V, and 12V configurations
- High energy density
- Long design life
- Up to two year shelf life
- Wide operating temperature range:  
-40°C to +50°C



## Construction

- Positive plates - pure lead grids manufactured using a unique process
- Negative plates - provide perfect balance with the positive plates to ensure optimum recombination efficiency
- Separators - superior quality microporous glass mat separator with high absorption and stability
- Containers and lids - UL94 V-0 rated flame retardant material, highly resistant to shock and vibration (J types are PPE+PS resin, all others are ABS)
- Electrolyte - high grade dilute sulphuric acid absorbed into separator material
- Terminal design - leak resistant patented dual seal terminal design

- Self-regulating pressure relief valves - prevent ingress of atmospheric oxygen
- Flame arrestors - built into each bloc for increased operational safety

## Installation and Operation

- PowerSafe® SBS batteries are designed for use in cabinets or on stands, close to the point of use. A separate battery room is not required
- Cells and monoblocs can be mounted in any orientation except inverted
- Recommended float charge voltage: 2.29Vpc @ 20°C (68°F) or 2.27Vpc @ 25°C (77°F)
- Up to two year shelf life
- Low maintenance: no water addition required

- Several PowerSafe SBS battery types are also available for underwater applications

## Standards

- Designed to be compliant with international standard IEC 60896/21 & 22
- Classified as "Long Life" according to Eurobat guide 1999
- Conforms to Telcordia® SR-4228
- Recognised by UL (UL Standard 1989)
- Approved as non-spillable cargo for ground, sea and air transportation in accordance with US DOT Regulation 49 and ICAO & IATA Packing Instruction 872
- The management systems governing the manufacture of PowerSafe SBS products are ISO 9001:2008 and ISO 14001:2004 certified

## General Specifications


Battery Type	Number of Cells	Nominal Voltage (V)	Nominal Capacity (Ah)		Nominal Dimensions (mm)			Typical Weight (kg)	Short Circuit Current (A) <sup>(2)</sup>	Internal Resistance (mΩ) <sup>(2)</sup>	Terminals
			10 hr rate to 1.80Vpc @ 20°C	8 hr rate to 1.75Vpc @ 77°F	Length	Width	Height				
SBS 8	6	12	7	7	138	86	99	2.7	455	27.1	2 x M4 F
SBS 15	6	12	14	14	200	77	140	5.7	891	13.5	2 x M6 M
SBS 30	6	12	26	26	250	97	156	9.5	1556	7.9	2 x M6 M
SBS HB30 <sup>(1)</sup>	6	12	26	26	250	97	156	9.6	1556	7.9	harness
SBS 40	6	12	38	38	250	97	206	12.7	2184	5.6	2 x M6 M
SBS 60	6	12	51	51	220	121	261	18.5	2618	4.4	2 x M6 M
SBS 110	3	6	115	116	200	208	239	21.2	3804	1.7	2 x M8 M
SBS 130	3	6	132	133	200	208	239	22.7	4111	1.4	2 x M8 M
SBS 300	1	2	310	307	200	208	239	21.7	8700	0.23	2 x M8 M
SBS 390	1	2	360	361	200	208	239	23.2	11101	0.18	4 x M8 M
SBS J13 <sup>(3)</sup>	6	12	12	12	175	83	129	5.2	957	13.0	2 x M6 F
SBS J16 <sup>(3)</sup>	6	12	15	15	181	76	167	6.7	1111	11.0	2 x M6 F
SBS J30 <sup>(3)</sup>	6	12	26	26	166	175	125	11.8	1766	7.0	2 x M6 F
SBS J40 <sup>(3)</sup>	6	12	39	39	197	165	170	17.4	2400	5.2	2 x M6 F
SBS J70	6	12	64	64	329	166	174	27.6	3500	3.5	2 x M6 F
SBS B8	6	12	31	31	280	97	159	10.3	1270	10.0	2 x M8 F
SBS B8F	6	12	31	31	303	97	159	10.3	1270	10.0	2 x M6 M
SBS B10	6	12	38	38	280	97	184	12.8	1390	9.0	2 x M8 F
SBS B10F	6	12	38	38	303	97	184	12.8	1390	9.0	2 x M6 M

Notes:


<sup>(1)</sup> SBS HB30 battery is fitted with a 533mm/21 inch harness that terminates in a 2-pin polarised plug-in connector, which is compatible with embedded power SLC systems.

<sup>(2)</sup> Figures obtained via IEC method.


<sup>(3)</sup> Optional metal jackets are available for SBS J types. To order an SBS J type with a metal jacket add "X" to the part number (eg: "SBS J13X").




SBS 8 to 60 types  
SBS J types



SBS 110-390 types



SBS B8 & B10 types



SBS B8F & B10F types



www.enersys-emea.com

**EnerSys**  
World Headquarters  
2366 Bernville Road  
Reading, PA 19605  
USA  
Tel: +1 610 208 1991  
+1 800 538 3627  
Fax: +1 610 372 8613

**EnerSys EMEA**  
EH Europe GmbH  
Löwenstrasse 32  
8001 Zürich  
Switzerland

**EnerSys Asia**  
152 Beach Road  
Gateway East Building  
Level 11  
189721 Singapore  
Tel: +65 6508 1780

Contact:

© 2013 EnerSys. All rights reserved.  
Trademarks and logos are the property of EnerSys and its affiliates, except Telcordia®, which is not the property of EnerSys.